
# Laserliner

# **MultiFinder Pro**

# Universal detector for locating wood, metal, copper, iron and live wires










- Several integrated sensors make the MultiFinder Pro a scanning and detection tool for many different applications.
- One-button operation to switch between the different measurement modes
- The user guide on the LC display makes the MultiFinder Pro easy and reliable to use.
- Auto-Calibration: adjusts the device to different surfaces immediately after switching on.
- Auto-Cal Plus: allows objects to be localized easily in Metal-Scan mode.
- Acoustic and visual detection signals for finding
- High safety is guaranteed by the permanent voltagewarning function.
- Special feature: in metal mode, it is even able to detect concealed lines when they are not live.



# Voltage



ARTICLE	ARTICLE NO	EAN-CODE	PU
MultiFinder Pro	080.966A	4 021563 703630	5











## **TECHNICAL DATA**

**DETECTION RANGE AC** 110 - 230V, 50 - 60 HZ

### MEASURING DEPTH

- 1. Wood/metal beam location (Stud-Scan)
- Up to 4 cm depth
- 2. Targeted metal location:
- Ferro-Scan/ Non-Ferro-Scan (Metal-Scan) Up to 10 cm / up to 5 cm depth
- 3. Targeted location of live supply lines (AC-Scan) Up to 4 cm depth
- Location of dead supply lines Up to 4 cm depth

**AUTOMATIC CALIBRATION Yes** 

**PERMANENT VOLTAGE WARNING Yes** 

**DISPLAY** Illuminated LCD

**DETECTION AND WARNING INFORMATION** Visual and audible

**OPERATING CONDITIONS** 0°C ... 40°C , Max. humidity 80% rH, no condensation, Max. working altitude 2000 m above sea level

### STORAGE CONDITIONS

-20°C ... 70°C, max. humidity 80% rH

### POWER SUPPLY

1 x 9V alkali battery (type 6LR 61)

**DIMENSIONS** (W x H x D)

80 x 186 x 40 mm

WEIGHT (incl. battery)



### **MultiFinder Pro** inclusive softbag

+ battery

Packing dimension (W x H x D)